

SPECIFICATIONS:

Compressor Type:

Belt Driven, IOO% duty cycle, VMAC oil-injected rotary screw

Rated Air Capacity:

30 CFM @ IOO PSI (I50 PSI max)

Engine:

Honda GX390 air cooled 4-stroke OHV with electric start, EPA and CARB compliant, Honda approved application

System Weight (wet):

Approx. 93 kg (205 lbs)

Dimensions:

60.7cm (H) x 54.4cm (W) x 85.lcm (L) / 23.9" (H) x 21.4" (W) x 33.5" (L)

Mounting Plate:

48.6cm (W) x 63.5cm (L) 19.125" (W) x 25.0" (L)

Decibels (dB) @ 20 feet:

67 - 8I dB

Fuel Tank Capacity:

6.I Litres (I.6 gallons)

Battery (included):

12V, 210CCA, 260CA

Safety Features:

Compressor thermal protection circuit, automatic rapid blow-down valve on tank, 200 PSI pressure relief valve, low engine oil pressure shutoff

Warranty:

TECHNI Lifetime Warranty on VMAC air compressors *; one year on all other major components; for details, visit: www.technisystems.co.uk

*For more information about Techni Systems Warranty Policy, please visit: www.technisystems.co.uk



Techni Limited

Sundorne Trade Park, Henley Way Shrewsbury SYI 4NS +44 (0)|743 443|76 info@technisystems.co.uk

VMAC EUROPEAN DISTRIBUTOR

Sales - Installation - Service

FIND OUT MORE



SCAN ME

LICHTWEIGHT - AFFORDABLE COMPACT . POWERFUL.

AR COMPRESSOR







technisystems.co.uk

THE **G30** IS THE **MOST AFFORDABLE** AIR **COMPRESSOR** ON THE

proved their undisputed technical and

of other rotary screw air compressors, it is also

30 CFM. 100% OF THE TIME

includes a patented 30 CFM rotary screw air of the time, so you don't need an air receiver tank. Get

50% LIGHTER & SMALLER

Techni Systems G30 petrol driven air compressors are engineered and manufactured for mobile applications.

INDUSTRY-LEADING RELIABILITY

compressors come with the industry's first Lifetime Limited

LIGHT WEIGHT AFFORDABLE EASY TO OPERATE







SYSTEM COMPONENTS

FUEL TANK

6.I L (I.6 gallons)

LIFTING HOOK •

ENGINE THROTTLE •--CONTROL

Controlled by system air pressure, idles up/ down automatically with air demand

FUEL SUPPLY •

ENGINE •

Honda GX390

OHV; EPA and CARB-compliant

air-cooled 4-stroke

Manual choke, Fuel

on/off

TECHNI SYSTEMS BELT-DRIVE SYSTEM

Gearless, clutchless, auto-tensioned serpentine belt, steel belt-guard

TECHNI SYSTEMS WHASP

Integrated oil/air separator and air/oil cooler (patent pending)



UNLOADER

Decreases engine load, lowers sound levels, reduces fuel use and engine wear

TECHNI SYSTEMS AIR COMPRESSOR

Oil-injected rotary screw; 30 CFM @ 100 psi; 100% duty cycle; up to 150 psi

G30 QUICK FACTS

ELECTRONIC KEY SWITCH

Electric start; hour meter

Powerful 100% duty cycle means you can fill a tractor trailer tyre in 180 seconds.

Included I2V, 2IOCCA,

BATTERY

260CA

- Rotary screw compressors have a long history of superior **performance** and durability.
- Smooth air delivery **eliminates** the need for receiver tanks in most applications. No need for

OPTIONAL EQUIPMENT

REMOTE CONTROL PANEL

Part No.: 3101.0141

Remote control panel with a ten foot extension for key switch, hour meter, choke, and unloader



"The Honda has a lower idle speed, creating less noise, which is much appreciated when used in residential areas. There is zero lag on air tools under high demand. We've been using VMAC for so long that old issues have been forgotten."

-Chris Binks, Assistant Manager, KAL TIRE



